



ANYANG HIGHRISE METAL MATERIALS CO., LTD.

Add: Qugou Industrial Zone, S301 Anlin Road, Yindu District, Anyang  
455000, Henan Province, China.

## HOT PRODUCTS LIST

Item	Specification (%)	Usage
Silicon Metal	<b>Si Metal 2202</b> Si 99.5 min, Fe 0.20, Al 0.20, Ca 0.02 max 10-100mm	Alloying Material for Aluminum Alloy
	<b>Si Metal 3303</b> Si 99.2 min, Fe 0.30, Al 0.30, Ca 0.03 max 10-100mm	
	<b>Si Metal 441</b> Si 99.0 min, Fe 0.40, Al 0.40, Ca 0.1 max 10-100mm	
	<b>Si Metal 553</b> Si 98.5 min, Fe 0.50, Al 0.50, Ca 0.3 max 10-100mm	
	<b>Si Metal Off-Grade</b> Si 97.0 min, Fe 2.0, Al 1.0, Ca 1.0 max 10-100mm	
Magnesium Metal	<b>Mg 9990</b> Mg purity 99.90% min 75.kg/ingot	Alloying Material for Aluminum Alloy
	<b>Mg 9995</b> Mg purity 99.95% min 75.kg/ingot	
Ferro Silicon	<b>FeSi 72</b> Si 72.0 min, Al 2.0, C 0.2, P 0.04, S 0.02 max 10-100mm	Deoxidizer for Steelmaking; (Grains used as Inoculant in Casting)
	<b>FeSi 75</b> Si 75.0 min, Al 2.0, C 0.2, P 0.035, S 0.02 max 10-100mm	
Ferro Silicon Briquette	<b>FeSi Briquette 65</b> Si 65.0 min, Al 3.0, C 3.0, S 0.1, P 0.05 max 30-50mm	Deoxidizer for Steelmaking and Casting
Medium Carbon Ferro Manganese	<b>FeMn75C2.0</b> Mn 75.0 min. C 2.0 max, P 0.3 max, S 0.3 max. 10-70mm	Deoxidizer and Mn Additive in Steelmaking
	<b>FeMn78C1.5</b> Mn 78.0 min. C 1.5 max, P 0.3 max, S 0.3 max. 10-70mm	

<b>Aluminum Titanium Boron Master Alloy</b>	<b>AlTi5B1</b> Ti 5.0% B 1.0% Fe 0.3% max, Si0.2% max. Dia. 9.5mm	Master Alloy for Aluminum
<b>Low Carbon Ferro Chrome</b>	<b>LC FeCr</b> Cr 60% basis, C 0.1 max, Si 1.5 max, S &P 0.3 max 10-70mm	Cr Additive in Steelmaking
<b>Silicon Slag Briquette</b>	<b>Si Briquette 50</b> Si 50.0 min, C 8.0, Al 7.0max, S 0.1max, P 0.05 max 30*50mm	Deoxidizer for Steelmaking & Casting (Substitute of Ferrosilicon)
	<b>Si Briquette 65</b> Si 65.0 min, C 5.0, Al 7.0max, S 0.1max, P 0.05 max 30*50mm	
<b>Silicon Slag</b>	<b>Si Slag 50</b> Si 50.0 min, C 8.0 max, Al 7.0max, S 0.1max, P 0.05 max 0-5mm	Deoxidizer for Steelmaking & Casting (Substitute of Ferrosilicon)
	<b>Si Slag 55</b> Si 55.0 min, C 8.0 max, Al 7.0max, S 0.1max, P 0.05 max 0-5mm	
	<b>Si Slag 60</b> Si 60.0 min, C 8.0 max, Al 7.0max, S 0.1max, P 0.05 max 0-5mm	
<b>Silicon Carbide</b>	<b>SiC 88</b> SiC 88.0 min, F.C. 4.0, Fe2O3 2.0 max 0-10mm	Deoxidizer, Desulfurizer for Steelmaking;
	<b>SiC 97</b> SiC 97.0 min, F.C. 1.0, Fe2O3 1.5 max 0-10mm	
<b>Silicon Carbide Briquette</b>	<b>SiC Briquette 65</b> SiC 65.0 min, Fe2O3 3.0, Al2O3 5.0 max 30*50mm	Inoculant for Casting
	<b>SiC Briquette 70</b> SiC 70.0 min, Fe2O3 3.0, Al2O3 5.0 max 30*50mm	
<b>FeSiMg</b>	<b>FeSiMg6RE1</b> RE 0.5-2.0, Mg 5.0-7.0, Ca 3.0 max, Si 42.0% min. 5-50mm	Noduziler for Casting
<b>Recarburizer</b>	<b>Granular Graphite</b> Fixed Carbon 95% min. S 0.05% max. Diameter 6mm granules	Carbon Raiser for Casting